

R3-GUICRAT

3" LINE VOLTAGE GU-10 REMODEL HOUSING



Project

Location

PRODUCT DESCRIPTION



R3-GUICRAT housing is designed for IC rated ceilings when using an LED lamp and Non-IC when using a Halogen Lamp Accommodates up to 10W LED GU-10 lamp or 50 W GU-10 lamp

SPECIFICATIONS

HOUSING: IC Rated when using an LED lamp Max. 10 watt Can have direct contact with insulation Non IC when using a Halogen lamp Max 50 watt. 3" clearance on all sides from insulation required

Height: 4 ¼"

Cut out: 3 ¼"



AIR FLOW RESTRICTION: Airtight models are designed to restrict air flow from room into plenums in compliance to the WSEC-Washington State Energy Code (less than 2.0 CFM-Cubic Feet per Minutes)

MOUNTING: Supplied with (3) high tension remodeling clips designed to secure the housing to an existing sheet rock ceiling.

JUNCTION BOX: Pre-wired, galvanized steel J-box (25 cubic-inch) with (4) knock-outs. Strain clamps and ground wire. Equipped with safety standard thermal protector rated for 90°C.

LABELS: ETL/CETL listed (ETL listed number: 4005878) ETL listed for through-branch wiring (4) No. 12 AWG 90°C and damp locations.

COMPATIBLE TRIMS

Model	Model
R3-409	R3-460
R3-421	R3-488DG
R3-488	R3-4763
R3-493	R3-4765
R3-508	R3-560
R3-509	R3-5760
R3-521	R3-5763
R3-555	R3-5765
R3-559	R3-5778
R3-588	R3-588DG
R3-590	R3-DS90
R3-593	R3-5970
R3-DR88	R3-DS589
R3-DR488	R3-DS88